



1D Wired Laser barcode scanner

Features

- High resolution up to 4 mil.
- Multi - selection for different usage.
- Multi-interfaces just by change cable.
- Optional: auto-sensing and hands-free stand.
- Suitable for Supermarket, POS (Point-of-sales), inventory management or Document tracking.



Scanners Specifications :

Model Name	LS6300F	LS6320F
Description	Cable / Auto-sensing	
Engine	RIOTEC 1D laser engine	

Performance Characteristics

• Light Source	650 nm Laser Diode
• Depth of Field(13 mil)	200 mm
• scan rate	60 scan /sec
• Best Resolution	0.1 mm (4 mil) - Code 39
• Print Contrast	40% or more
• Scan Angle	Yaw 65°, Rotation 30°, Pitch 55°
• Indicators	LED & beeper
• Interface	USB HID,USB Serial (by request) , RS232(by request)
• Auto-sensing	Up to 150 mm
• Symbologies	Code39, Code39 Full ASCII ,Code32,UPC-A, UPC-E, EAN-13,EAN-8,Code93 , Code128,Codabar,Interleaved 2of 5, MSI,Code11 ,Matrix 2 of 5 ,ISBN, ISSN, ITF 14, ,GS1 Databar,GS1-128

Electrical Characteristics

• Input voltage	5 VDC ±5%
• Current - operating	85mA max

Features

• Dimension (L * W * H)	165 X 65 X 90 mm
• Weight	114g +/- 5 g (No cable)

Features

• Temperature-operation	0°C to 50°C
• Temperature-storage	-10°C to 60°C
• Humidity-operation	5% to 95% relative humidity, non-condensing
• Humidity-storage	5% to 95% relative humidity, non-condensing
• Ambient Light	Fluorescent Light 300 lux to Sun Light 30000 lux

Depth of Field (There are +/- 1 cm tolerance)

• 4 mil Code39	30mm - 110 mm
• 5 mil Code39	30mm - 130 mm
• 13 mil EAN 13	30mm - 200 mm

Product specification is subject to change without notice.

RIOTEC CO., LTD.

8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan

EL : +886-2-8647-1828

FAX : +886-2-8647-1800

-mail : sales@riotec.com.tw

Web : www.riotec.com.tw